

# COPYRIGHT:

DEUTSCH

DIESE DRUCKSCHRIFT UND ALLE IHRE BESTANDTEILE IST URHEBERECHTLICH GESCHÜTZT.

ABBILDUNGEN, GRAFISCHE DARSTELLUNGEN, TEXTE ODER DIE DRUCKSCHRIFT INSGESAMT ODER IN TEILEN DÜRFEN NICHT OHNE VORHERIGE SCHRIFTLICHE GENEHMIGUNG NACHGEDRUCKT ODER SONST REPRODUZIERT WERDEN (Z. B. AUF CD-ROM ODER IM INTERNET).

WENN SIE DIESE PDF-DATEI FÜR IHREN PERSÖNLICHEN GEBRAUCH VON UNSERER INTERNET-SEITE KOPIERT HABEN, MÖCHTEN WIR DARAUF HINWEISEN, DASS ALLE DORT ZUR VERFÜGUNG GESTELLTEN DATEIEN OHNE JEDEN WEITERN HINWEIS AUF DEN NEUSTEN TECHNISCHEN STAND GEBRACHT WERDEN. DIE ÄNDERUNG VON TECHNISCHEN DATEN UND LIEFERUMFANG IST DAHER VORBEHALTEN.

# COPYRIGHT:

## ENGLISH

ALL ARTWORK, PICTURES AND TEXTS ARE COVERED BY OUR COPY-RIGHT.

THEY MUST NOT BE COPIED FOR REPRODUCTION (E.G. ON CD-ROM DISKS OR INTERNET-SITES) OR USED IN THEIR ENTIRE FORM OR IN EXCERPTS WITHOUT OUR PREVIOUS WRITTEN AGREEMENT.

IF YOU ARE DOWNLOADING PDF-FILES FROM OUR INTERNET HOME-PAGE FOR YOUR PERSONAL USE, MAKE SURE TO CHECK FOR UPDATED VERSIONS.

WE CANNOT TAKE ANY LIABILITY WHATSOEVER FOR DOWNLOADED FILES, AS TECHNICAL DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# ARRI



## ARRIHEAD 2

ARRIHEAD 2 -  
the compact geared head

Smaller, lighter in weight and equally efficient is the formula of the future. The ARRIHEAD 2 is its successful product. With an equal equipment range and operating convenience, it is 8 cm shorter and approximately 4 kg's lighter than the large ARRIHEAD. With this design, the ARRIHEAD 2 is an ideal production tripod head not only for 35 mm cameras, but also for 16 mm filming.



Tilt Angle .....	+/- 30 degrees w/o wedgeplate. +/- 90 degrees with wedgeplate Wedgeplate increments are 20, 25, 30, 40, 50 and 60 degrees.	
Camera Mounting .....	Sliding base for ARRI quick-release bridgeplate and other touch ,n' go systems. ± 140 mm balance adjustable system. ARRI Bridgeplate System.	
Cradle .....	Tilt Drive via precision drive chain/pulleys, user adjustable tension V-cradle rails, ball bearings.	
Tilt/Pan Drive .....	<u>Tilt</u> Laterally moveable tilt handle up to 38 degrees to right. Selectable 3 Speed gear. Drive, plus neutral.	
	<u>Tilt Speeds</u> Slow – 17.5 turns for 60 degrees full tilt. Medium – 9.25 turns for 60 degrees full tilt. Fast – 4.75 turns for 60 degrees full tilt.	
	<u>Pan Speeds</u> Slow – 65 turns for full 360 degrees pan Medium – 35.5 turns for full 360 degrees pan. Fast – 19 turns for full 360 degrees pan.	
Lock Off Brakes and Friction Levers .....	<u>Tilt</u> , two individual positive lock off brakes. <u>Pan</u> , single positive lock off brake. Note: Lock and friction levers located near hand wheels.	
Gear Head Base .....	Standard Mitchell.	
Miscellaneous .....	Self illuminating level. Removeable wheel handle. 2 holding knobs for accessory box. Viewfinder support bracket. 4 threaded rosettes (2 per side).	
Weight .....	With wedge and quick release bridgeplate                    15 kg, 33 lbs. Tilt/Pan wheels                2,5 kg, 5,5 lbs	
Temperature Range .....	- 20°C degrees to + 50°C degrees - 4°F degrees to + 122°F degrees	
Max.Load .....	50 kg, 110 lbs	
Dimensions:		
With Handwheels .....	Height	330 mm/13 inch
	Length	566 mm/22 inch
	Width	343 mm/13 inch
Without Handwheels .....	Height	305 mm/12 inch
	Length	468 mm/18 inch
	Width	267 mm/11 inch

- Battery bracket 2 and special accessory shoe
- Reduction gear for tilt and pan, ratio 1:5
- Big handwheels
- Universal handgrip
- Adapter 2 for ARRI bridgeplate system